

TIGRE 3200



LITTLE BIG FRIEND

The **Tigre** is the most compact equal wheel tractor of the Antonio Carraro range. This fantastic “**All rounder**” was designed to satisfy a multitude of activities associated with the management of parks, gardens, sports fields, communal areas and small agricultural plots.

The features that set the Tigre models from the Series 15 apart are basically reliability, comfort and safety. In particular the **Antonio Carraro** full chassis with oscillation **ACTIO™** is synonymous with an equal weight distribution, maximum grip, minimum ground compaction, first class operative comfort.

The four wheel drive, along with ACTIO™, guarantee maximum comfort and operative safety in that they grant constant traction and grip.

The environmentally reliable 4 stroke diesel engine with 12 speed mechanical gearbox with 12 forward and 8 reverse speeds, offer a complete speed range in both directions, along with a substantial saving in running costs.

Its great versatility allows the operator to work in a variety of environments every day of the year; for this reason each owner of the Tigre will discover he has a friend for all seasons.

ANTONIOCARRARO.COM



ECCELLENZA ITALIANA

TECHNICAL DATA: **TIGRE 3200**

Chassis	Full chassis with oscillation ACTIO™ • Steerable wheels • Four equal wheel drive	
Engine Type	Diesel a iniezione indiretta Emissions regulations: Stage 5 N° cylinders: 3 Max engine rpm: 3000 Fuel tank capacity (l.): 21	Output kW/HP (97/68/CE): 18,9/ 25,7 Max. torque (Nm/rpm): 67,8/2000
Transmission	12-speed mechanical gearbox: 8 forward and 4 reverse speeds	
PTO	Standard at 540 rpm and synchronised with all gearbox speeds	
Shaft	ASAE profil 1" 3/8 with 6 splines	
Rear hydraulic lift	Rear with 3-point hitch (cat. 1) - Capacity (Kg): 825	
Brakes	Rear-axle and parking brakes	
Steering	Hydraulic	
Weight	960 Kg	
Tyres	7.50-16 6.50-16 7.5L-15 29x12.50-15 STG 29x12.50-15 GARDEN	
Dimensions	Wheelbase: 1100 Lenght: 2600÷2660	Front overhang: 860 Height: 2010÷2040
Standard equipment	Front and rear independent differential lock • Adjustable, sprung seat • Safety belts • Foldable safety roll bar • Multiple-hole draw-bar • Tow hook • Horn • Lights • Power socket • Braking and turning indicators • Series of control lights • Tachometer/revolution counter • Safety starting switch	
Optional	Rear revolving working light • Wheel ballasts • Single acting hydraulic outlet with rear quick coupling • Mudguards widening for wide wheels	

